



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
COM	COM	NC	NC	NC	NC	5E	5D	5C	5DP	4E	4D	4C	4DP	3E	3D	3C	3DP	2E	2D	2C	2DP	1E	1D	1C	1B
PIN	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50
COM	1A	1F	1G	2B	2A	2F	2G	L	3B	3A	3F	3G	4B	4A	4F	4G	NC	5B	5A	5F	5G	NC	NC	NC	NC

CUSTOMER NAME	REV.	DESCRIPTION	DATE	TYPE	TN POSITIVE/REFLECTIVE	THIRD ANGLE:	MODEL NO.						
CUSTOMER P/N				VIEWING DIRECTION	6 O'CLOCK		GS-07024AA	GLORY SOUND (ASIA) LTD					
VI-503				DRIVING METHOD	STATIC Vop=4.5V	UNSPECIFIED:	DWG.	DATE	CHK.	DATE	APPR.D.	DATE	PAGE
QTN NO.				OPERATING TEMP.	-20°C TO +70°C	± 0.2mm	XLY	07/07/10					2 OF 2
				STORAGE TEMP.	-30°C TO +80°C	UNSPECIFIED:							
				CONNECTION	PIN	± 0.5°							